# Plastic adaptor with 7 outlets for spray nozzles

Product code: Plastic adaptor with 7 outlets 3/4-1/8F FRPP-IN (# 200982)

A plastic adaptor that can attach multiple spray nozzles.

- Up to seven spray nozzles can be mounted per adaptor.
- No piping work! Easy installation—Just screw in spray nozzles to an adaptor.
- Much more economical than a stainless steel adaptor.


## **Product photo**



#### ■ Features

- Made of glass-fiber reinforced polypropylene (FRPP).
- ●Heat-resistance: 80 °C (176 °F).
- Possible spray flow rate: max. 84 L/min at
  0.3 MPa (when 12 L/min nozzle x 7 are mounted).
- Much more compact and lightweight than a metal adaptor.
- Affordable price, due to injection-molding.
- ●Inlet size (pipe connection): Rc3/4 (3/4" BSPT female threaded)
- Outlet size (nozzle connection): Rc1/8 (1/8" BSPT female threaded) x 7

#### Drawing




## ■ Applications

- Spraying: Chemical washer, rain tester
- Washing: Beverage tanks, pasteurizer
- Water fountains, entertainment, mist sauna, and more

# ■Photos of product with spray nozzles attached, Spray photos



Adaptor with 7 hollow cone spray nozzles



Adaptor with 7 full cone spray nozzles



Adaptor with 7 flat spray nozzles






(3)

# **■**Example of uses

Rain test chamber



Chemical washer



Mist sauna




Tank cleaning



Fog and light displays



Fountain



## ■How to order

## Product code: Plastic adaptor with 7 outlets 3/4-1/8F FRPP-IN (#200982)

Please also select a 1/8M (R1/8 threaded) spray nozzle from our wide lineup. Contact us for details.



### **Headquarters**

Daiichi Kyogyo Bldg., 1-15-15, Awaza, Nishi-ku, Osaka 550-0011, Japan Tel: 81-6-6538-4015 Fax: 81-6-6538-4022

Email: overseas@kirinoikeuchi.co.jp

URL: https://www.kirinoikeuchi.co.jp/eng/